



MODEL 204-3

2-Piece 3-Way
Sanitary Ball Valve
T-Clamp

Pressure Rating	1000WOG
Material	ASTM A351-CF8M
Seat	Cavity filled PTFE
Bore Type	Standard bore
Additional Features	<ul style="list-style-type: none"> L-port, T-port available ISO5211 direct mounting pad

MATERIALS LIST

NO.	PART NAME	QTY	MATERIAL
1	BODY	1	CF8M
2A	CAP	1	CF8M
2B	CAP	2	CF8M
3	BALL	1	CF8M
4	BALL SEATS	4/1 SETS	PTFE
4A	BALL SEATS	2/1 SETS	PTFE
4B	BALL SEATS	2/1 SETS	PTFE
5	STEM	1	SUS316
6	THRUST WASHER	1	PTFE
7A	END SEALS	1	PTFE
7B	END SEALS	2/1 SETS	PTFE
8	STEM PACKING	1 SETS	PTFE
9	THRUST WASHER	1	TFM1600
10	GLAND BUSH	1	SUS304
11	BELLEVILLE WASAER	2	SUS304
12	STOP	1	SUS304
13	HANDLE NUT	2	SUS304
14	WASHER	1	SUS304
15	HANDLE	1	SUS304
16	HANDLE SLEEVE	1	VINYL
17	LEVER STOP	1	SUS304
18	LEVER STOP NUT	1	SUS304
19	O-RING	1	VITON
20	STUFF	1	PTFE

DIMENSIONS(mm)

SIZE	d	d1	d2	d3	L	H	D	F	A	N	M	E	H1	ISO 5211	
														(1)	(2)
1/2"	12.5	9.4	20.32	25	133	68	9	67	8.2	6	6	131	36.8	F04	F03
														42	36
3/4"	12.5	15.75	20.32	25	142	68	9	71	8.2	6	6	131	36.8	F04	F03
														42	36
1"	20	22.1	43.64	50.4	160	94	11	80	11.5	6	7	184	55.1	F05	F04
														50	42
1 1/2"	32	34.8	43.64	50.4	182	114	14	91	15.1	7	9	227	75.2	F07	F05
														70	50
2"	38	47.5	56.34	64	216	123	14	108	15.1	7	9	227	84.4	F07	F05
														70	50

TYPE	PORT	1	2	3	4
T					
L					

